

Crescent 41kg Ice Maker - Self Contained





Model Number

### **PRODUCT FEATURES**

- · Individually shaped crescent ice.
- Protected by HoshiGuard Antimicrobial Agent.
- CycleSaver® technology includes a double-sided evaporator, uniquely crafted in stainless steel, which produces ice on both sides, resulting in more ice in less amount of time.
- EverCheck™ Control Board with audible alarm and diagnostic features, designed to assist service technicians in diagnosing problems.
- Accessible digital operation panel allows for easy identification of operation status and cause of faults.
- · Automated cleaning function makes cleaning simple and saves time.
- Durable stainless-steel exterior.
- Easily removable & cleanable air filters on front panel.
- Accessories: Manual, Scoop, check valve, Hex Bolt legs and 150mm adjustable legs included (water filter and optional hex bolt legs sold separately)

### **TECHNICAL DRAWING**







For free 6 month extended warranty, register online within 4 weeks of purchase date. hoshizaki.com.au











## PRODUCT SPECIFICATION

	Production Capacity / 24hrs	Approx. 41kg @ 21°C Air temp; 15°C Water Approx. 33kg @ 32°C Air temp; 21°C Water
	Max Storage Capacity	Approx. 16kg
	Freeze Cycle Time	Approx. 23 Min (At. 21°C Air ; 15°C Water)
	Ice Production / cycle	Approx. 0.71kg/80pcs
	Dimensions	452mm (W) x 610mm (D) x 988mm (H) (982-1005mm (H) with 150mm adjustable legs)(842mm (H) with hex bolt leg)
	Cooling	Air
	Weight Net/Gross (kg)	39/49
	Refrigeration System	Forced Air Circulation
	AC Supply Voltage	1 PHASE 220-240V 50Hz / 10amp Plug
	Amperage	Running: 1.4A Starting: 7.7A
	Refrigerant Charge	R290/68g
	Operating Conditions:	
	Ambient Temp	7-38°C
	Water Supply Temp	7-32°C
	Water Supply Pressure	0.07-0.8MPa (0.7-8bar)
	Voltage Range	±6%
	Electrical consumption	Rated Motor: 220W (Power Factor: 69%)
	Water Consumption / 24hrs	Approx. 0.12m <sup>3</sup> /d(AT. 21°C; WT 15°C)

# **INSTALLATION REQUIREMENTS**

- Qualified plumber required for installation.
- · Allow 15cm clearance at rear, sides and top for proper air circulation and ease of maintenance.
- Hoshizaki recommends the use of a compatible water filter to prevent non-warrantable s cations.

<sup>\*</sup>Refer to manual for full installation & maintenance requirements.