



Model Number  
91000916

- Individual premium crescent cube with no ice bridging.
- Exceptionally hard crystal-clear cubes that melt slowly.
- Durable stainless-steel exterior.
- Slide in air filter at front for easy cleaning -maintaining performance efficiency.
- Double-sided stainless-steel evaporator for all water conditions -produces more ice in less cycles.
- Flush mount to rear wall.
- Good in hard water areas.
- Snap in water tank design – easy to remove for sanitisation.
- Low electrical consumption.
- Low water consumption.
- LED lights and audible alarms.
- Comes standard with Hex Bolt legs for underbench installation.



**CRESCENT ICE**

Weight: 9g

**HEIGHT**

842mm (H) with included hex bolt leg or  
982-1005mm (H) with included 150mm adjustable legs

Production Capacity / 24hrs      Approx. 52kg @ 21°C Air temp; 15°C Water  
Approx. 37kg @ 32°C Air temp; 21°C Water

Max Storage Capacity	Approx. 23kg
Freeze Cycle Time	Approx. 26 Min (At. 21°C Air ; 15°C Water)
Ice Production / cycle	Approx. 0.96kg/110pcs
Dimensions	605mm (W) x 610mm (D) x 842mm (H) including hex bolt legs 988mm (H) with 150mm adjustable legs
Cooling	Air
Weight Net/Gross (kg)	45/57
Refrigeration System	Forced Air Circulation
AC Supply Voltage	1 PHASE 220-240V 50Hz / 10amp Plug
Amperage	Running: 1.6A Starting: 8.5A
Refrigerant Charge	R290/90g
<b>Operating Conditions:</b>	
Ambient Temp	7-38°C
Water Supply Temp	7-32°C
Water Supply Pressure	0.07-0.8MPa (0.7-8bar)
Voltage Range	±6%
Electrical consumption	Rated Motor: 255W (Power Factor: 63%)
Water Consumption / 24hrs	Approx. 0.14m <sup>3</sup> /d(AT. 21°C ; WT 15°C)

- Pump out Drain - Maximum height (H) 1.5metres at length (L) 5metres, Maximum height (H) .5metres at length (L) 15metres.
- Reduced installation time: Internal drain pump simplifies installation task.
- Plug and play efficiency: Easy drain connection without complications.



For free 6 month extended warranty, register online within 4 weeks of purchase date.  
[hoshizaki.com.au](http://hoshizaki.com.au)

- Ensure the condenser is cleaned periodically as per the manufacturer's manual.
- Do not plug the unit into multi-plug power boards with other appliances
- Installation Consider room ventilation or installing air conditioning to improve environment working conditions.
- Hoshizaki recommends the use of a compatible water filter to prevent non-warrantable scale & sediment complications.

\*Refer to manual for full installation & maintenance requirements.

Descriptions and specifications are subject to change at any time, without notice.  
Illustrations for demonstration purposes. Copyright © 2023 Hoshizaki Lancer Pty Ltd. All right reserved.