



FM405

icemachinesdirect 

EUROPEAN MACHINES LOWEST PRICES GUARANTEED

Technical features

- Electronic control
- Stainless steel bodywork - scotch brite
- Air or water cooled
- Direct trasmission
- Easily accessible components
- Low power and water consumption
- Reduced dimensions
- Continuous production
- Refrigerant R290



Matching bins

Machine	Bins		kg

Voltage

230/50/1 Standard version

Technology and Certifications



Type of ice

Flake ice



Residual water content 15 %



Machine dimensions

Net size WxDxH	538 x 663 x 650 mm
Net weight	78 kg
Shipping size WxDxH	610 x 760 x 820 mm
Shipping weight	87 kg


**Factory 12, Sandown Square
56 Smith Rd
Springvale Vic 3171**



FM405

icemachinesdirect 

EUROPEAN MACHINES LOWEST PRICES GUARANTEED



Operating Limits

	Minimum	Maximum
Air temperature	10°C	43°C
Water temperature	5°C	38°C
Water pressure	1 bar	5 bar
Electrical voltage	-10 %	+10 %

Specifications and design
are subject to change without notice

Model	Voltage	Daily pro- duction kg	Power input Watt (*)	Refrigerant		Fuse A	Consumptions (**)		
		10°C/10°C		Type	Charge kg		kWh/ 100kg	kWh/ 24h	Water l/h
FM405	230/50/1	300	1000	R290	0.150	16	22.7	n.a.	8.3

(*) Power Input: at 43°C Ambient Temperature

(**) Water Consumption: at 32°C Air and 21°C Water